

-1-

METHOD AND SYSTEM FOR CONFIGURING AN AIR INTERFACE IN A MODEM

FIELD OF THE INVENTION

The present invention relates to a method and system for data transmission and reception in a modem. In particular, the present invention relates to a method and system for configuring an air interface for data transmission and reception in a modem according to multiple standards.

BACKGROUND OF THE INVENTION

Generally, modems have been designed to work with one of many existing standards. For example, while there are many air interface, or radio link, standards, most current modems are designed to operate with only one of them. Even within a particular standard, uplink and downlink formats are very different, and require separately designed air interface processors. Clearly, this results in increased costs for both design and hardware when a new standard is implemented, and precludes using a modem designed to work with one standard from being reconfigured to work with a different standard.

An alternative approach to a hardware implementation is a software implementation in which the air interface and related modules are completely programmable. This is similar to the concept of a software radio. However, a serious disadvantage of the software approach is the slower throughput of the air interface since software solutions typically have much more overhead than hardwired solutions and run much slower. For example, it would not be unreasonable to expect a software implementation to run an order of magnitude slower compared to a hardware implementation.

It is therefore desirable to provide an air interface processor that can be configured for more than one standard, or data format while avoiding the undesirable constraints of a purely software implementation.

-2-

SUMMARY OF THE INVENTION

It is an object of the present invention to provide a method and system that obviates or mitigates at least one disadvantage of the prior art. It is a particular object of the present invention to provide a method and system for configuring an air interface in a modem for multiple data and transmission standards and formats.

According to the invention, an air interface processor for a modem includes a programmable event handler, a programmable microsequencer and configurable data processing units such as a frame formatter. By data processing we refer generally to the processing of data including its examination, modification and manipulation. Data processing includes: the insertion of additional data bits to data and packaging the data in a specific format, for example, as performed in a typical frame formatter; discarding data bits and sorting data for queuing, for example, as performed in a frame deformatter; and other data related operations such as those performed in an FEC encoder or FEC decoder.

Accordingly, the modem and the air interface processor are programmable since the event handler and the microsequencer are programmable. They are also configurable since the data processing units (as well as the microsequencer and event handler as discussed below) are configurable. The modem and the air interface processor are also configurable in the sense that they can be configured to accommodate a standard or format by selecting which programs the event handler and microsequencer are to execute and loading the selected program into these devices along with any required setup operations.

In a first aspect, the present invention provides an air interface processor for a modem, comprising an event scheduling unit for scheduling the processing, by at least one data processing unit in the modem, of data to be transmitted by the modem; and a control unit for receiving instructions from the event scheduling unit and determining commands to send to the at least one data processing unit.

According to another aspect of the present invention, there is provided a method of processing data in a modem, comprising scheduling the processing of data for transmission by the modem; transmitting the schedule to a microsequencer; and sending commands to a frame

-3-

formatter to build a frame of data in accordance with a program of the microsequencer.

According to a further aspect of the present invention, in a modem having configurable means for converting data into formatted data packages and programmable control means for controlling the configurable data conversion means, a method of controlling the conversion of data comprises configuring the configurable data conversion means in accordance with at least one communication standard; selecting one of the at least one communication standards; and programming the programmable control means in accordance with the selected communication standard to control the configurable data conversion means.

According to a still further aspect of the present invention, there is provided an air interface processor for a modem, comprising an event scheduling unit for scheduling the processing, by at least one data processing unit in the modem, of data received by the modem; and a control unit for receiving instructions from the event scheduling unit and determining commands to send to the at least one data processing unit.

According to a still further aspect of the present invention, there is provided method of processing data in a modem, comprising scheduling the processing of data reception by the modem; transmitting the schedule to a microsequencer; and sending commands to a frame deformatter to extract data from a frame of data in accordance with a program of the microsequencer.

According to a still further aspect of the present invention, in a modem having configurable means for extraction of data from formatted data packages and programmable control means for controlling the configurable data extraction means, a method of controlling the extraction of data comprises configuring the configurable data extraction means in accordance with at least one communication standard; selecting one of the at least one communication standards; and programming the programmable control means in accordance with the selected communication standard to control the configurable data extraction means.

The present inventions, therefore has the advantage of allowing a modem to be programmable to accommodate different standards while operating significantly faster than a corresponding software implementation.

-4-

According to a still further aspect of the present invention, there is provided a method of programming a microsequencer to perform a multi-way branching instruction based on m sets of n conditions, the method comprising: establishing m lookup tables, each table having entries indexed by the n conditions of one of the m sets of n conditions, and each entry of each
5 table having a lookup value; defining m functions, each function based on one of the m sets of n conditions; and determining, based on the m functions, the next program instruction to execute.

Advantageously, the multi-way branching instruction can be implemented in hardware to process the instruction much faster than a corresponding software implementation such as consecutive IF-THEN statements.

BRIEF DESCRIPTION OF THE DRAWINGS

Additional details of present invention will now be described, by way of example only, with reference to the attached Figures, wherein:

Figure 1 is a block diagram of a modem incorporating an air interface processor according to the present invention;

Figure 2 is a block diagram of an air interface processor according to the present invention;

Figure 3 is a chart of event handler instruction sets according to the present invention;

Figure 4 is a chart of register access instructions according to the present invention;

Figure 5 is a chart of data scheduling instructions according to the present invention;

Figure 6 is a chart of burst descriptor instructions according to the present invention;

Figure 7 is a chart of a modulator burst information field format according to the present invention;

Figure 8 is a chart of a demodulator burst information field format according to

-5-

the present invention;

Figure 9 is a chart of a processor wait instruction according to the present invention;

5 Figure 10 is a chart of a microsequencer instruction set according to the present invention;

Figure 11 is a chart of a microsequencer memory format according to the present invention;

Figure 12 is a block diagram of a configuration of condition codes and forks according to the present invention;

10 Figure 13 is an example of fork values according to the present invention;

Figure 14 is an example of three events to be transmitted by a device of the present invention;

Figure 15 illustrates the events of Figure 17 as stored in an event handler of the present invention;

15 Figure 16 illustrates programs or sequences of instructions within a microsequencer of the present invention;

Figure 17 is a terminal modulator block diagram in accordance with the present invention;

20 Figure 18 is a block diagram illustrating the components of the forward error correction unit of Figure 20;

Figure 19 illustrates different headers stored in the frame formatter in accordance with the present invention;

Figure 20 illustrates different characteristic polynomials accommodated by the Reed-Solomon encoder in accordance with the present invention;

25 Figure 21 illustrates a formatted frame structure in accordance with the present invention;

Figure 22 is a terminal demodulator block diagram in accordance with the present invention; and

-6-

Figure 23 is a block diagram illustrating the components of the forward error correction decoder of Figure 22.

DETAILED DESCRIPTION OF THE INVENTION

5 An embodiment of the present invention will now be described. Figure 1 shows a modem 30 incorporating an air interface processor (AIP) 32 having a modulator air interface processor 40 and a demodulator air interface processor 140 which are associated with the modulator 36 and demodulator 38, respectively. Both the modulator 36 and the demodulator 38 have special-purpose processors that are designed with the intention of allowing the modem 30 to meet any air interface standard. However, it is impossible to predict whether all forthcoming LMDS and SatCom systems can be handled. For any systems which cannot be handled directly, there will be a provision to bypass internal FEC (forward error correction) generation/correction and process a raw bit stream.

10 The air interface processor 32, is shown schematically in Figure 2, and is divided into the modulator air interface processor 40 and the demodulator air interface processor 140. Each processor 40, 140 includes an event scheduling unit known as an event handler 44 and control means, for example, a control unit known as a microsequencer 46, 146. In Figure 2, different microsequencers 46 and 146 are illustrated for the modulator air interface processor 40 and the demodulator air interface processor 140, respectively. Different microsequencers 46, 146 are preferred in the embodiment of Figure 2 in order to accommodate different instruction sets associated with data transmission and receipt. However, it is fully contemplated that the same microsequencer can be used for both sides. For convenience, we will refer to the microsequencer 46 unless a distinction is needed.

15 The event handler 44 provides an abstraction of the burst frequency time plan; the microsequencer 46 controls how data is processed by the modulator/demodulator circuitry including means for the conversion of data into formatted data packages, such as frame formatter 50 and means for extracting data from formatted data packages, such as frame deformatter 150. According to the present example, the frame formatter 50 and the frame deformatter 150 are

20

-7-

configurable, for example, to accommodate existing communication standards. Thus, for example, a frame formatter 50 can be instructed to format data in accordance with any one of a number of different standards. The algorithm used by the frame formatter 50 is predetermined, however, parameters used by the frame formatter, for example by way of register values, can be manipulated to configure the frame formatter to accommodate different standards and formats.

In the present embodiment, both the microsequencer 46 and the event handler 44 are hardware units programmable to accommodate different transmission standards and formats. Both the microsequencer 46 and the event handler 44 are also configurable, for example, by setting register values or setting the mode in which the device will operate (e.g. burst mode or continuous mode). In particular, the microsequencer 46 is configured by software at start up and configuration of the microsequencer 46 is intended to be static during the course of operation (though this is not a necessary condition). The event handler 44 configuration is static for continuous mode operation, and dynamic for burst mode to accommodate varying burst frequency time plans.

The primary purpose of the event handler 44 is to schedule the processing of burst data transmission/arrival in the modem 30. (Continuous data is treated as a special subset of burst data). In addition to being able to initiate sending/receiving bursts of data, the event handler 44 has the ability to perform various ALU operations, and to perform conditional or unconditional branches. The ALU and branch operations are performed simultaneously, which allows for greater code density than would otherwise be possible.

The instruction set is divided into general purpose and modem control instructions. There are 8 16-bit read/write registers, and 8 16-bit read-only registers. All instructions occupy one 48-bit word in memory. The instruction set summary is shown in Figure 3. The event handler 44 memory is a single-port, synchronous, 1K * 48 RAM.

Type 1, general-purpose instructions (bits 47:46=00) are comprised of an ALU instruction and a two-way branch instruction. These ALU instructions are similar to standard ARM RISC processor ALU instructions. Note that the second operand always passes through a programmable barrel shifter before being applied to the ALU.

-8-

For each operation, the ALU computes a new result and the flags associated with that result (N=negative, Z=zero, C=carry, V=overflow). The results of the ALU operation are stored in the destination register only if the 'W' flag is asserted for that instruction. The ALU flags are updated only if the 'S' flag is asserted.

5 The results of the ALU operation are written to a destination register (Rd). The destination register may be any of the 8 read/write registers (R0-R7). Operand 1 (Rn) is always a register, and may be any of the 16 registers. Operand 2 is either an immediate value (I=1) or a register value (I=0), and is passed through a programmable barrel shifter to yield a 16-bit result.

In general, each ALU instruction performs the following operation:

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

```

result = fn(Rn, shift(op2))
Rd      <= result if W else no change
{N,Z,C,V} <= flags(result) if S else no change

```

Standard ALU RISC and branch code operations are supported. The branch component of the instruction allows a conditional branch to happen based on the result of the previous ALU instruction. Each branch instruction has an address offset to jump to in the case the condition passes, and a separate address offset to jump to in the case the condition fails. This mechanism only allows for relative branches.

Register Access instructions (bits 47:46=01), as shown in Figure 4, are provided to allow reading or writing arbitrary registers within the modem 30. The modulator air interface processor 40 can only control registers within the modulator 36, and the demodulator 38 air interface processor 42 can only control registers within the demodulator 38. This facility is used to enable/disable internal ASIC blocks, and to control external devices that need to be manipulated on a real-time basis, such as RF frequency select for MF-TDMA systems. It is not intended for static configuration, which is better handled via the processor interface (although it can be performed here as well).

Rhi provides the top 16 bits of the 24 bit address. Rlo (bit 44=0) or imm_lo (bit 44=1) provides the bottom 8 bits. For a write operation (bit 45=0), the 32 bit data is contained

-9-

directly in the lower bits of the instruction. For a read operation (bit 45=1), the bottom 3 bits encode the number of the destination register. The register access occurs over the internal HCPU bus.

Data scheduling instructions (bit 47=1), as shown in Figure 5, are the means by which bursts of data are transmitted or received by the modem 30. Each of these instructions is an entry that maps time indices to actions. Time indices are specified in clock ticks relative to the start of a super-frame. Time index 0 is determined via the PCR algorithm (PCR offset). Actions are pointers to microcode instruction sequences. With this scheme, it is not necessary to count frames or even timeslots, only superframes.

For the execute phase of a data scheduling instruction, the event handler 44 will wait until the current time (time index relative to super-frame start) is approximately equal to the trigger time. (It can only wait for the times to be approximately equal because the event handler 44 runs off the byte clock, whereas the current time is a counter that runs off the sample clock.) When the trigger time is reached, a start command is sent to the microsequencer 46, which will begin running at the address specified in "microsequencer address".

A time offset of 32'hFFFF_FFFF is a special code indicating that this event is to be processed immediately. The microsequencer address 0 is a special code indicating that the start command should not be sent.

If the trigger flag is set, the time offset in the current event is passed to the preamble insert module (not shown) in the modulator 36, or direct sampling module (not shown) in the demodulator 38.

Bursts can be conditional on the availability of data in a certain queue. In this case, the 'D' flag must be set to 1, and 'Q' must be set to the number of the data queue which must contain data (0 → DATA1, 1 → DATA2, etc).

For burst mode applications, the air interface processor 32 provides a special BURST instruction, as shown in Figure 6, which is used to specify special information related to the following burst of data.

The contents of the burst info field are different for the modulator 36 and

-10-

demodulator 38. For the modulator 36, as shown in Figure 7, this field is used to select which preamble is to be used for the following burst (PS). Up to four preambles may be defined. For MF-TDMA applications, the burst info field contains frequency information that is used to reprogram the DDS or Fractional-N counter.

5 For the demodulator 38, as shown in Figure 8, the burst info field is used to select the expected preamble for the incoming burst (PS). Up to four preambles may be defined. It also contains the length of the expected burst. The SB7016 tags all incoming bursts with an arbitrary user ID, which the MAC layer software can use to correlate received bursts with expected bursts in the BFTP. The user ID is specified in the burst info field.

10 Figure 9 shows a typical processor wait instruction.

The microsequencer 46 is responsible for sending commands to the frame formatter 50/ deformatter 52. On the modulator 36, this builds up a frame of data on a byte-by-byte basis.

15 The core of the microsequencer 46 design is based on a modified version of the AMD2910 micro-program sequencer. The original 2910 is a 12 bit sequencer with a 32 word stack, and is capable of conditional branching, subroutine calls, and looping. The microsequencer 46 in the air interface processor 32 is a 10 bit sequencer, but adds some powerful instructions, as shown in Figure 10, to perform multi-way conditional branching, among other things.

20 The number of microcode sequences is limited only by the available sequence RAM (SeqRAM) available. The SeqRAM is a single-port synchronous 1K * 32 RAM.

The microsequencer 46 has a program counter (PC), which is initially set by the event handler 44. When it is instructed to start by the event handler 44, it shall begin executing the instructions in SeqRAM at the specified address, until such time as a JZ (jump-to-zero) instruction is found.

25 The memory format for the modulator microsequencer 46 is shown in Figure 11.

The EMIT field is used as an argument to the OP CODE field, and is used for branch addresses or to load the internal counter. The SR field (scrambler reset) can be used to reset the scrambler at any time.

-11-

The FORK instruction, which is an addition to basic 2910 instruction set, uses the value formed by the fork_cc(3:0) vector as the basis for a 16-way branch. For example, if the value of fork_cc is 12, the microsequencer 46 will advance its program counter by 12.

- 5 The fork_cc value is updated every clock cycle based on the configuration circuitry shown in Figure 12. Each bit in fork_cc is derived from a programmable look-up table. A 5-bit value is used as the index to this look-up table.

	bit 4	bit 3	bit 2	bit 1	bit 0
FORK LUT 0	insert_pcr	end of message in queue 1	counter < threshold	counter == threshold	r0
FORK LUT 1	insert_pcr	end of message in queue 2	counter < threshold	counter == threshold	r1
FORK LUT 2	insert_pcr	end of message in queue 3	counter < threshold	counter == threshold	r2
FORK LUT 3	insert_pcr	end of message in queue 4	counter < threshold	counter == threshold	r3

Table 1: FORK LUT Indices

- 10 Programming the FORK instruction is a rather convoluted process, as it involves three layers of indirection. The FORK instruction is essentially a "case" statement. The idea is to generate a 4-bit value (fork_cc) to create an offset of 0 to 15. Each bit of fork_cc is derived from the corresponding FORK LUT. Each FORK LUT is indexed by the 5-bit number formed by the concatenation of the conditions shown in Table 1. The conditions r0, r1, r2, and r3 are bits from the R7 register in the event handler 44. The R7 bit select register can be used to select
 15 among the lower 8 bits of the R7 register. Refer to Figure 12 for more details. The FORK instruction, as illustrated in Figure 12, is implemented in hardware using memory means for the lookup tables and multiplexers to define corresponding functions fork_cc(0) to fork_cc(3). By memory means, we include any suitable storage means including hardware circuits such as read-only memory. This hardware implementation allows parallel decision making resulting in a much

-12-

more efficient and faster solution than a corresponding software solution, for example, sequential conditional statements.

For example, suppose we wanted `fork_cc(0)` to evaluate as true whenever `insert_pcr` and `counter==threshold` are both true. This condition can be expressed as `1xx1x`, which means that bits 4 and 1 must be 1, and the other bits are don't cares. In this case, we would program the bits in the LUT that match `1xx1x` with 1, as shown in Figure 13, and the others with 0. The value generated is `32'hCCCC_0000`.

In this example, `fork_cc(0)` is a boolean function of the 5 conditions of Table 1 and its values are defined by the lookup table of Figure 13. For example, referring to the second row of 13, `fork_cc(0)(0,0,0,0,1)` is 0 as indicated by the lookup value in the "match" column. Of course, referring to Table 1, the arguments 0,0,0,0,1 represent the conditions: `insert_pcr` is false; end of message in queue 1 is false; `counter < threshold` is false; `counter == threshold` is false; and `r0` is true, respectively. Changing the lookup values in the lookup table of Figure 13 will change the corresponding function `fork_cc(0)`. In that sense, a function such as `fork_cc(0)` can be configured by setting the lookup values of the corresponding lookup table. Note that we use "function" to include the possibility that "don't care" relationships may exist, as illustrated in the example. The vector function `fork_cc(3:0)` is simply the vector equivalent of `fork_cc(3)` to `fork_cc(0)`.

In the example of the present embodiment, it is desirable to have 16 way branching, based on a 5 bit index value. It is, of course, fully contemplated that multi-way branching is possible for fewer or more than 16-way branching and the invention is not confined to 5 bit index values (i.e. based on 5 conditions) and that other sizes of index values are possible.

The present example illustrates how the FORK instruction can be used to program a microsequencer. However, it is fully contemplated that the FORK instruction can be used in programming any suitable microprocessor.

The condition codes (CCSEL) for conditional branches (for example, CJV) in the microsequencer 46 are hard-coded as follows:

-13-

Condition Code	Description
0	always false
1	counter != 0
2	counter == threshold
3	counter < threshold
4	counter <= threshold
5	insert_pcr == 1
6	end of message in queue 1
7	end of message in queue 2
8	end of message in queue 3
9	end of message in queue 4
10	insert_pcr ==1 AND end of message in queue 1
11	insert_pcr ==1 AND end of message in queue 2
12	insert_pcr ==1 AND end of message in queue 3
13	insert_pcr ==1 AND end of message in queue 4
14	value of R7(bit 9)
15	value of R7(bit 8)

Register R7 in the modulator 36 event handler 44 can be used to control the microsequencer 46 to some degree. Bits 8 and 9 of the R7 register are used to generate condition codes 14 and 15. Bits 0 to 7 of the R7 register, in conjunction with the static R7 Bit 5 Select register, can be used as inputs to the FORK LUT.

The read-only event handler 44 registers for the modulator 36 contain the following values:

-14-

Register	Description
R8	Bytes remaining in message, queue 1
R9	Bytes remaining in message, queue 2
R10	Bytes remaining in message, queue 3
R11	Bytes remaining in message, queue 4
R12	Condition Code Register
R13	Event Handler Program Counter
R14	32'h0000_0000
R15	32'hFFFF_FFFF

The definition of FFCMD (frame formatter command) is shown in Table 2. This instruction set is used to generate frames to be fed into the modulator frame formatter 50. As data or control words are inserted, they can be flagged with an attribute indicating whether or not they should be scrambled, and which outer code is to be used (ie. Reed-Solomon, CRC, or neither). If the SB bit is asserted in the microsequencer 46 instruction, the scrambler is bypassed. The value in the OC field is used to select which outer coding scheme is to be used (0-3).

The frame formatter is also able to insert register values from the event handler 44 into the data stream. This mechanism allows the generated data stream to be more dynamic than would otherwise be possible. When the event handler 44 issues a start command to the microsequencer 46, the contents of R0 to R7 are passed through a programmable barrel shifter and stored as inputs to the frame formatter 50.

-15-

Command	Description	Name
0	nop	NOP
1 – 16	Insert Control Word 1 – 16	CW1 – CW16
17 – 24	Insert Shifted Register 0 – 7	R0 – R7
25	Insert Original PCR	PCRO
26	Insert Current PCR	PCR
27	Insert Data from Queue 1	DATA1
28	Insert Data from Queue 2	DATA2
29	Insert Data from Queue 3	DATA3
30	Insert Data from Queue 4	DATA4
31	Flush	FLUSH

Table 2: Modulator Command Set for Frame Formatter

The most common use of the barrel shifter is to align an 8-bit value in one of the registers to the upper 8 bits of the 16-bit register value (inputs to the frame formatter 50 must be MSB-aligned). The barrel shifter is configured as follows:

47:42	41:36	35:30	29:24	23:18	17:12	11:6	5:0
R7 shift	R6 shift	R5 shift	R4 shift	R3 shift	R2 shift	R1 shift	R0 shift

Each Rx shift field is defined as follows:

5	4	3	2	1	0
shift_by					
2'b00 = LSL (Rn, shift_by)					
2'b01 = LSR (Rn, shift_by)					
2'b10 = ASR (Rn, shift_by)					
2'b11 = ROL (Rn, shift_by)					

10

A simple microcode sequence to generate an MPEG frame for a base station could be programmed in the following manner. This sequence indicates that all bytes except for the

-16-

initial sync should be scrambled (".S") MPEG_FRAME:

```

CONT      CW1.OC1      # 1 byte, typically 47h
CONT      CW2.S.OC1    # 1 byte
CONT      CW3.S.OC1    # 1 byte
5  CONT      CW4.S.OC1    # 1 byte
LDCT      182  DATA2.S.OC1      # send data from queue
2, load counter
loop:     RPCT loop DATA2.S.OC1      # continue pulling data
from queue 2
10          # until counter reaches zero; total =
184
JZ        FLUSH          # indicates end of burst; soft
reset

```

The device can act as a simple ATM segmentation engine by setting the control word to a 5-byte ATM header. Up to 16 simultaneous ATM connections can be handled in this manner (one per control word).

```

ATM_CONN_1:
CONT      CW1.S.OC1      # CW1 = 5-bytes = { VPI/VCI=(a,b)
}
LDCT 2    NOP          # 4 NOPs because CW1 is 5 bytes
loop1:    RPCT loop1    NOP
LDCT 46   DATA1.S.OC1      # send 48 bytes from queue 1
loop2:    RPCT loop2    DATA1.S.OC1
25        JZ          FLUSH

```

Figure 14 illustrates a specific example illustrating the working of the event handler and microsequencer of the present invention. In the example there are three time slots 60, 62, 64 which have been assigned to a terminal by the system. The first and second time slots 60, 62 are normal time slots at times $t = 200$ and $t = 400$ respectively. The third time slot 64 is a bandwidth on demand time slot at time $t = 900$. Time is relative to the beginning 66 of the super frame as indicated in Figure 14 at $t = 0$.

-17-

Three events corresponding to time slots 60, 62, 64 are stored in the event handler 44 as shown in Figure 15. At or near the time of the first event, $t = 200$, the event handler 44 sends a request to the microsequencer 46, to execute a sequence of instructions or program to handle a normal time slot.

Referring to Figure 16, the microsequencer 46 contains programs directed at different time slot requirements and standards. For example, a first program 68, identified by the logical name TS in Figure 16, is a program which will prepare a single ATM cell for transmission in a normal time slot. Note that Figure 16 illustrates the steps of each program at the highest level of abstraction for the purposes of the present example. Of course, the specific commands in the program consist of instructions from the instruction set previously discussed.

Figure 17 is a schematic drawing illustrating the functional relationship between the event handler 44, the microsequencer 46 and the devices or modules which they control. Referring to Figures 16, 17 and 21, the first step of program TS 68 instructs the frame formatter 50 to use a 4 byte header 102 in accordance with a normal time slot. Referring to Figure 19, different headers 72, 74 are stored as data within the frame formatter 50 itself. This facilitates the ability to configure the frame formatter 50 and to accommodate different transmission standards in accordance with the present invention. The specific 4 byte header 102 used by program TS 68 is Header_1 72 stored in the frame formatter 50. A plurality of headers can be stored in the configurable frame formatter 50 and the number of headers is only constrained by the size of the storage space available and the choices made in implementation of the invention.

The present invention is able to handle as input data either a raw data stream or formatted data such as ATM cells depending on how the device is programmed. In the present example, input data is packaged in 53 byte ATM cells and stored in the input data queue 80. The microsequencer 46 is kept informed of the status of the input data queue 80 as indicated by reference 81. The next step of program TS 68 is to instruct the frame formatter 50 to extract from the input data queue 80 a 53 byte ATM cell for transmission. The frame formatter 50 then appends this ATM cell to the Header_1 72 to form the header and data portions 102, 104 of the formatted frame structure 100.

-18-

The program then instructs the forward error correction unit 82 to perform the necessary operations. Referring to Figure 18, forward error correction in the terminal modem includes Reed-Solomon encoding, differential encoding, convolutional encoding, insertion of unique word and preamble insertion as is known in the art. Program TS 68 instructs the Reed-Solomon (RS) encoder 84 to perform RS encoding according to a suitable characteristic polynomial, for example, RS (204, 188, 16) illustrated in Figure 20 as polynomial_1 94. The RS encoder 84 is, however, configurable and it contains instructions in accordance with different characteristic polynomials 94, 96 to facilitate different configurations in accordance with the present invention.

Following RS encoding, the program instructs the differential encoder 86, convolutional encoder 88, and other modules 90, 92 to handle error correction coding. This results in an additional 16 byte error control block 106 appended after the header and data portions 102, 104 of the formatted frame structure 100 as illustrated in Figure 21. Although not illustrated in the figures, a guard interval of one or more bytes may be appended to the end of the structure to prevent overlap between consecutively transmitted time slot structures.

Once program TS 68 of the microsequencer 46 has completed assembling the formatted frame structure 100, the structure 100 is passed onto the modulator 36 for transmission by antenna 83.

Returning to the event handler 44, once it has instructed the microsequencer 46 to handle the first event at time $t = 200$, the event handler 44 remains idle until the next event at time $t = 400$. At that time, the event handler 44 instructs the microsequencer 46 to handle the second event, which in the present example, requires another normal time slot. Accordingly, the event handler 44 instructs the microsequencer 46 to execute the program TS 68 which assembles a second one ATM cell data package with the next ATM cell in the input data queue 80 and passes the package onto the modem 36 for transmission.

The event handler 44 is active again at the time $t = 900$ when event 3 requires a bandwidth on demand data transmission. Referring to Figure 16, a second program, program BOD 70 in the microsequencer 46 is directed to preparing a data package having 3 ATM cells for

-19-

transmission in a bandwidth on demand time slot.

Program BOD 70 begins by instructing the frame formatter 50 to use a header 102 in accordance with a bandwidth on demand time slot. This 4 byte header 102 has a structure similar to the header of a normal time slot and is represented as Header_2 74 in Figure 19.

5 Program BOD 70 then instructs the frame formatter 50 to fetch from the input data queue 80 three ATM cells which are appended to the Header_2 74.

Program BOD 70 then instructs the forward error correction unit 82 to perform coding and other operations needed to control errors. As in the case of program TS 68, an additional 16 bytes of data 106 are generated from this process and appended at the end of the formatted frame structure 100 for transmission by the modem 36 using antenna 110.

10 Of course, other frame formats not included in this example can be implemented as well. For example, another structure is the mini time slot structure which is used to transmit small amounts of data not bandwidth efficient for the normal time slot structure. Mini time slots are typically implemented within the duration of one normal traffic time slot and always occur at the end of a frame period. The type of data accommodated by mini time slots include
15 information for management, signaling and ranging.

Mini time slots can be accommodated in the device of the previous example by programming the event handler 44 to recognize such events and including a program in the microsequencer 46 to build a suitable data structure, with corresponding changes in other modules
20 such as the inclusion of a new header in the frame formatter 50.

Normal, mini and bandwidth on demand time slots are used by repetitive super frames in burst mode links. A characteristic of burst mode is that time slot size need not be constant and can vary depending on the type of time slot structure assigned by the system. Thus the event handler 44 is continuously modified by software in burst mode, depending on the burst
25 frequency plan scheduled by the system.

An alternative approach supported by the present invention is continuous link mode in which a fixed frame structure is always repeated by the event handler 44. Thus, the header 102 always follows a single format, the data 104 remains a constant number of bytes and the size of

-20-

the error control block 106 is fixed. In effect, continuous mode link is a special case of burst mode link and the device of the present invention can be programmed to operate in this fixed way.

With reference to Figures 14 to 18, although the example described above has been in respect of the transmit side of a modem, the invention applies equally to the receive side. Referring to Figure 22, details of a demodulator are illustrated. As noted earlier, a different microsequencer 146 can be used on the receive side.

Data received using antenna 183 is demodulated by demodulator 136. The data is then decoded by FEC decoder 182 and processed by frame deformatter 150 before going to output queue 180. The actions of these components are controlled by event handler 44 and microsequencer 146. The microsequencer 146 is kept informed of the status of the output data queue 180 as indicated by reference 181.

Figure 23 provides details of FEC decoder 182. Specifically, FEC decoder 182 includes convolutional decoder 190 followed by differential decoder 188, sync detector 186 and Reed-Solomon decoder 184, as is well known in the art.

Furthermore, although the previous example has been with reference to a terminal modulator, the present invention is equally applicable to the base station. Specifically, the hardware Figures 2, 17 and 18 are the same for terminals and the base station, however, different modes are used. Similarly the present invention applies to the receive-side of the base station.

The above-described embodiments of the invention are intended to be examples of the present invention. Alterations, modifications and variations may be effected the particular embodiments by those of skill in the art, without departing from the scope of the invention which is defined solely by the claims appended hereto.